



Max. operating temp. 200° F. .

Polypropylene not recommended for use with chromic or nitric acids. See chemical resistance chart for compatability.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAMCO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAMCO IS PROHIBITED

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ± 1/8
 ANGULAR: MACH ± BEND ±
 TWO PLACE DECIMAL ±
 THREE PLACE DECIMAL ±

MATERIAL
 POLYPROPYLENE
 FINISH ---
 DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	TNH	09/08/08
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		

COMMENTS:
 3/32 PERFORATION
 NOT ACTUAL SIZE

POLYPROPYLENE RECTANGULAR
 DIPPING BASKET

TAMCO INDUSTRIES
 Tank Manufacturing and Fabrication

1390 Neubrecht Road
 Lima, Ohio 45801

SIZE STOCK NO.	#14223	REV.
A		
SCALE: none	WEIGHT:	SHEET 1 OF 1