



Max. operating temp. 200° F. .

Polypropylene not recommended for use with chromic or nitric acids. See chemical resistance chart for compatability.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAMCO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAMCO IS PROHIBITED

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ± 1/8
ANGULAR: MACH ± BEND ±
TWO PLACE DECIMAL ±
THREE PLACE DECIMAL ±

MATERIAL
POLYPROPYLENE
FINISH --
DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	TNH	01/14/08
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		

COMMENTS:
3/16 PERFORATION
NOT ACTUAL
SIZE

POLYPROPYLENE RECTANGULAR
DIPPING BASKET

TAMCO INDUSTRIES
Tank Manufacturing and Fabrication

1390 Neubrecht Road
Lima, Ohio 45801

SIZE/STOCK NO.	#14226	REV.
A		
SCALE: none	WEIGHT:	SHEET 1 OF 1