



DRUMSAVER™ INSERT FOR STEEL DRUMS

PRODUCT DESCRIPTION: The 55 is an accordion-style, seamless, vacuum-formed insert for 55-gallon open-head steel drums. Flexible accordion-pleat side-walls accommodate variations in drum heights, a common issue with reconditioned drums. The 55 is molded from FDA-approved low-density polyethylene. A contoured lip snaps over the top bead to prevent leakage between the insert and the drum wall, while also providing easy drum closure using a standard ring and bolt or lock assembly.

Insert Specifications

MATERIAL USED

Low-density polyethylene

INSERT DIMENSIONS

Diameter: 22.5" (+0.25"/-0")

Height: 33" - 34.5"

Average thickness: 15 mil (+/-10%)

WEIGHT

21 oz. (+/-10%)

SIDE-WALL DESIGN

Accordion

TEMPERATURE PARAMETERS

High (momentary): 175° (195°)F

Low: -40°F

Packaging Specifications

CARTON WEIGHT

38 lbs.

CARTON DIMENSIONS

Length: 35"

Width: 21"

Height: 15"

QUANTITY/CASE

20

PACKAGING STYLE

Rolled

TYPICAL APPLICATIONS: The 55 is designed for reconditioned drums because the accordion-style side wall design allows for a range of drum heights. The 55 is perfect for mixing, pumping and storing all liquids, powders and pastes that can be contained in low-density polyethylene. Examples include chemicals, inks, adhesives, greases, paints, coatings, silicones, and food. Can be used when rolling drums.

CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith.** CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

CDF CORPORATION • 77 Industrial Park Road • Plymouth, MA 02360
(800) 443-1920 • fax (508) 747-6333 • www.cdf1.com