

217 Bradley Hill Road, Blauvelt, New York 10913 (914) 353-3300 FAX: (914) 353-3376



CONTROLLED COPY
INITIALS AND DATE 91101

## TECHNICAL DATA SHEET F-217

CONSTRUCTION:

Low Density Polyethylene/Foamed Low Density Polyethylene/

Low Density Polyethylene

DESCRIPTION:

Three-ply co-extruded material:

Foamed Low Density Polyethylene Core Between Two Solid

Layers Of Low Density Polyethylene

**SPECIFICATIONS:** 

THICKNESS

AVAILABLE WEB WIDTH

.020" to .065" +/- .005" .065" to .090" +/- .007" .090" to .125" +/- .010"

1" to 25" +/- 1/16" 1" to 9" +/- 1/16" 1" to 9" +/- 1/16"

**DENSITY:** 

 $25 + \frac{1}{2} lbs/ft^3$ 

## CODE OF FEDERAL REGULATIONS COMPLIANCE:

21 CFR 177.1210; Closures with sealing gaskets for food containers

21 CFR 177.1520: Olefin polymers

21 CFR 178.2010: Antioxidants and/or stabilizers for polymers

21 CFR 175 300 : Resinous and polymeric coatings

FDA STATUS: The component materials of F-217 are listed under DMF 2434.

The aforementioned technical information and any recommendation are based on Tri-Seal's laboratory findings and are believed to be true and accurate, but we strongly recommend that our customers perform appropriate tests they feel necessary to insure the compatibility and stability of any given product with ours. Tri-Seal International guarantees to replace any quantity proved to be defective. We will not be held liable for any injury, loss or change, whether direct, incidental or consequential, due to the use of or inability to use the product or due to breach of warranty of any agreement existing between Tri-Seal and the purchaser. Unless contained in this data sheet or agreed to in writing by the officers of seller and user no other warrantee will be honored.

150216KH