# 7006

## 6 litre UV safe drum



 $For \ dimensional \ tolerances \ see \ table \ on \ next \ page$ 

Product part	Product code	Description	Material
Drum	7006B90-101	6 litre wide neck drum	HDPE
Lid	A7006-13-101	Screw lid	HDPE
Gasket	H14	Sealing gasket	Rubber

Capacity	Litres	Gallons
Brimful	6.2	1.64
When closed	6	1.59

Weight	Grams	Ounces
Drum	310	10.93
Lid	104	3.67
Gasket	6	0.21
Total	420	14.82

Colours	Colour code	PMS references
Container	Black 101	/
Lid	Black 101	/

#### Hazardous material information



Hazardous material type	Solids
Packaging group	I – II – III
UN marking	UN/1H2/X20/S//NL/CURTEC 1352
Maximum gross mass (kg)	X=20

Product identification	
1. Manufacturer ID	
2. Country of origin	(6)
3. Product no.	/
4. Food grade	/ 7
5. Material type	
6. Date clock	
7. UN mark	\ \( \) \\ \\ \\ \ \ \ \ \ \ \ \ \ \ \ \

#### Other information

All UV safe drums offer complete protection against UV-light within the 200-400 nm range Maximum filling temperature is  $70^{\circ}$ C/  $158^{\circ}$ F

Contents must have cooled to 30°C/86°F before containers can be closed and stacked

DoC available on request

UN certificate available on request

MVTR declaration available on request

User manual available on request

Wall thickness	mm
Minimal wall thickness	≥1.2
Nominal wall thickness	≥1.3

Dimensional tolerances	%
Height	±2.5
Diameter	±1.5

### Weight tolerance

All products have a tolerance of ±4% on the initial weight mentioned on this data sheet

© 2015 Property of CurTec International B.V. All rights explicitly reserved, it is not allowed to copy or communicate to other parties without written consent of CurTec.

