## 7015

## 15 litre UV safe drum



For dimensional tolerances see table on next page

Product part	Product code	Description	Material	
Drum	7015B00-101	15 litre wide neck drum	HDPE	
Lid	A7026-13-101	Screw lid	HDPE	
Gasket	H14	Sealing gasket	Rubber	

Capacity	Litres	Gallons
Brimful	15.3	4.04
When closed	15	3.69

Weight	Grams	Ounces
Drum	735	25.93
Lid	258	9.10
Gasket	15	0.53
Total	1008	35.56

Colours	Colour code	PMS references
Container	Black 101	/
Lid	Black 101	/



Hazardous material information	
Hazardous material type	Solids
Packaging group	1 – 11 – 111
UN marking	UN/1H2/X22/S//NL/CURTEC 1299
Maximum gross mass (kg)	X=22

Product identification	
1. Manufacturer ID	
2. Country of origin	
3. Product no.	
4. Food grade	
5. Material type	3
6. Date clock	1
7. UN mark	

Other information		
All UV safe drums offer complete protection	on against UV-light within the 200-400 nm range	
Maximum filling temperature is 70°C/ 158°F		
Contents must have cooled to 30°C/ 86°F	before containers can be closed and stacked	
DoC available on request		
UN certificate available on request		
MVTR declaration available on request		
User manual available on request		
Wall thickness	mm	
Minimal wall thickness	≥1.2	

Dimensional tolerances	%
Height	±2.5
Diameter	±1.5

≥1.3

## Weight tolerance

Nominal wall thickness

All products have a tolerance of  $\pm 4\%$  on the initial weight mentioned on this data sheet

© 2015 Property of CurTec International B.V. All rights explicitly reserved, it is not allowed to copy or communicate to other parties without written consent of CurTec.

