## 7026

## 26 litre UV safe drum



For dimensional tolerances see table on next page

| Product part | Product code | Description             | Material |
|--------------|--------------|-------------------------|----------|
| Drum         | 7026B00-101  | 26 litre wide neck drum | HDPE     |
| Lid          | A7026-13-101 | Screw lid               | HDPE     |
| Gasket       | H14          | Sealing gasket          | Rubber   |

| Capacity    | Litres | Gallons |
|-------------|--------|---------|
| Brimful     | 26.5   | 7       |
| When closed | 26     | 6.87    |

| Weight | Grams | Ounces |
|--------|-------|--------|
| Drum   | 920   | 32.45  |
| Lid    | 258   | 9.10   |
| Gasket | 15    | 0.53   |
| Total  | 1193  | 42.08  |

| Colours   | Colour code | PMS references |
|-----------|-------------|----------------|
| Container | Black 101   | /              |
| Lid       | Black 101   | /              |

| Hazardous material information |                             |
|--------------------------------|-----------------------------|
| Hazardous material type        | Solids                      |
| Packaging group                | 1-11-111                    |
| UN marking                     | UN/1H2/X33/S//NL/CURTEC 874 |
| Maximum gross mass (kg)        | X=33                        |

| Product identification    |     |     |
|---------------------------|-----|-----|
| 1. Manufacturer ID        |     |     |
| 2. Country of origin      |     |     |
| 3. Product no.            | /   |     |
| 4. Food grade             | /   | 1   |
| 5. Material type          |     | 4   |
| 6. Date clock             |     |     |
| 7. UN mark (on side wall) |     |     |
|                           | \ 6 | (5) |
|                           |     |     |
|                           |     |     |
|                           |     |     |

## Other information

All UV safe drums offer complete protection against UV-light within the 200-400 nm range Maximum filling temperature is 70°C/ 158°F

Contents must have cooled to 30°C/86°F before containers can be closed and stacked

DoC available on request

UN certificate available on request

MVTR declaration available on request

User manual available on request

| Wall thickness         | mm   |
|------------------------|------|
| Minimal wall thickness | ≥1.5 |
| Nominal wall thickness | ≥1.6 |

| Dimensional tolerances | %    |
|------------------------|------|
| Height                 | ±2.5 |
| Diameter               | ±1.5 |

| Weight tolerance  |
|---|
| All products have a tolerance of ±4% on the initial weight mentioned on this data sheet |

© 2015 Property of CurTec International B.V. All rights explicitly reserved, it is not allowed to copy or communicate to other parties without written consent of CurTec.

Last revision: 25 March 2015

