

EXTRAFLEX

04-300 SPECIFICATION SHEET

FEATURES

LINER

13g, Blue Engineered Yarn Liner

COATING

Black **HCT** MicroFoam Nitrile Palm Coating

BENEFITS:

ANSI Cut Level A3 EN Cut Level 5 "All in one": Fit, Feel, Flexibility, Breathability, Durability Excellent Wet Grip

CATEGORY:

Extraflex

APPLICATIONS:

Appliance Manufacturing Automotive Assembly Electronic Component Assembly HVAC/Sheet Metal Metal Fabrication Pulling Electrical Wires

Armor Guys reference number: 04-300

HCT EXTRAFLEX GLOSS GLOS

THUMB CROTCH

REINFORCMENT



 $C \in$



SPECIFICATIONS

LINER MATERIALS	Blue Engineered Yarn Liner				
COATING MATERIALS	Black HCT MicroFoam Nitrile				
WRIST DESIGN	Continuous Knit				
SIZES	XS -XXL				

PACKAGING								
CASE SIZE	XS	S	М	L	XL	XXL		
PER CARTON	120	120	120	120	120	120		
CASE WEIGHT	14.76/lbs	15.20/lbs	15.86/lbs	18.94/lbs	20.48/lbs	18.72/lbs		
CUFF COLOR	■Purple	■Red	Yellow	Brown	■Black	Light Blue		
ORIGIN	PRC							

PERFORMANCE LEVEL

EN388: 4542						
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70° C (158°F)

