

Hypro® Molded Flat Fan PVDF Spray Nozzles

Spray characteristics are even spray patterning, uniform spray distribution and high impact. Applications include car washes, carpet cleaning, stables, cooling, curing and much more. Colors may vary.

- Wears longer than SS or brass sprayers
- Excellent chemical & wear resistance



Color	Nozzle Size	Equivalent Orifice-Dia.	30	40	50	60	70	80	100	150	200	300	400	500	Spray Angle @ 40 PSI	Stock
Gray	02	.035"	.17	.20	.22	.24	.26	.28	.32	.39	.45	.55	.63	.71	25°	62487
Gray	03	.043"	.26	.30	.34	.37	.40	.42	.47	.58	.67	.82	.95	1.06	25°	62483
Gray	04	.052"	.35	.40	.45	.49	.53	.57	.63	.77	.89	1.10	1.26	1.41	25°	62506
Gray	05	.057"	.43	.50	.56	.61	.66	.71	.79	.97	1.12	1.37	1.58	1.77	25°	62478
Gray	06	.062"	.52	.60	.67	.73	.79	.85	.96	1.16	1.34	1.64	1.90	2.12	25°	62609
Terracotta	07	.067"	.61	.70	.78	.86	.93	.99	1.11	1.36	1.57	1.92	2.21	2.47	25°	60786
Moss Green	08	.072"	.69	.80	.89	.98	1.06	1.13	1.26	1.55	1.79	2.19	2.53	2.83	25°	60787
Gray	10	.079"	.87	1.00	1.12	1.22	1.32	1.41	1.58	1.94	2.24	2.74	3.16	3.54	25°	62658
Emerald Green	15	.094"	1.30	1.50	1.68	1.84	1.98	2.12	2.37	2.90	3.35	4.11	4.74	5.30	25°	60790
Gray	20	.110"	1.73	2.00	2.24	2.45	2.65	2.83	3.16	3.87	4.47	5.48	6.32	7.07	25°	62736
Gray	30	.142"	2.60	3.00	3.35	3.67	3.97	4.24	4.74	5.81	6.71	8.22	9.49	10.61	25°	62735
Gray	02	.035"	.17	.20	.22	.24	.26	.28	.32	.39	.45	.55	.63	.71	40°	62488
Gray	03	.043"	.26	.30	.34	.37	.40	.42	.47	.58	.67	.82	.95	1.06	40°	62543
Gray	04	.052"	.35	.40	.45	.49	.53	.57	.63	.77	.89	1.10	1.26	1.41	40°	62493
Gray	05	.057"	.43	.50	.56	.61	.66	.71	.79	.97	1.12	1.37	1.58	1.77	40°	62489
Gray	06	.062"	.52	.60	.67	.73	.79	.85	.95	1.16	1.34	1.64	1.90	2.12	40°	62608
Terracotta	07	.067"	.61	.70	.78	.86	.93	.99	1.11	1.36	1.57	1.92	2.21	2.47	40°	60836
Gray	08	.072"	.69	.80	.89	.96	1.06	1.13	1.26	1.55	1.79	2.19	2.53	2.83	40°	62544
Gray	10	.079"	.87	1.00	1.12	1.22	1.32	1.41	1.58	1.94	2.24	2.74	3.16	3.54	40°	62501
Gray	15	.094"	1.30	1.50	1.68	1.84	1.98	2.12	2.37	2.90	3.35	4.11	4.74	5.30	25°	62507
Gray	20	.110"	1.73	2.00	2.24	2.45	2.65	2.83	3.16	3.87	4.47	5.48	6.32	7.07	40°	62737
Gray	30	.142"	2.60	3.00	3.35	3.67	3.97	4.24	4.74	5.81	6.71	8.22	9.49	10.61	40°	62539
Gray	02	.035"	.17	.20	.22	.24	.26	.28	.32	.39	.45	.55	.63	.71	65°	62477
Gray	03	.043"	.26	.30	.34	.37	.40	.42	.47	.58	.67	.82	.95	1.06	65°	62491
Gray	04	.052"	.35	.40	.45	.49	.53	.57	.63	.77	.89	1.10	1.26	1.41	65°	62481
Yellow	05	.057"	.43	.50	.56	.61	.66	.71	.79	.97	1.12	1.37	1.58	1.77	65°	60846
Gray	05	.057"	.43	.50	.56	.61	.66	.71	.79	.97	1.12	1.37	1.58	1.77	65°	62738
Gray	06	.062"	.52	.60	.67	.73	.79	.85	.96	1.16	1.34	1.64	1.90	2.12	65°	62552
Gray	07	.067"	.61	.70	.78	.86	.93	.99	1.11	1.36	1.57	1.92	2.21	2.47	65°	62482
Gray	08	.072"	.69	.80	.89	.98	1.06	1.13	1.26	1.55	1.79	2.19	2.53	2.83	65°	62538
Gray	10	.079"	.87	1.00	1.12	1.22	1.32	1.41	1.58	1.94	2.24	2.74	3.16	3.54	65°	62490
Gray	15	.094"	1.30	1.50	1.68	1.84	1.98	2.12	2.37	2.90	3.35	4.11	4.74	5.30	40°	62492
Gray	20	.110"	1.73	2.00	2.24	2.45	2.65	2.83	3.16	3.87	4.47	5.48	6.32	7.07	65°	62500
Gray	30	.142"	2.60	3.00	3.35	3.67	3.97	4.24	4.74	5.81	6.71	8.22	9.49	10.61	65°	62611