

# Shrink Band Sizing Chart

Thread Diameter of Neck Finish	Finish Type	Finish Style	Recommended Layflat Dimension
13mm	425	Continuous Thread (CT)	28mm
15mm	425	Continuous Thread (CT)	28mm
18mm	400, 405	Continuous Thread (CT)	38mm
18mm	400	Child Resistant (CR)	38mm
18mm	Euro	Child Resistant (CR)	38mm
18mm	410, 415	Continuous Thread (CT)	38mm
20mm	400, 405	Continuous Thread (CT)	38mm
20mm	400	Child Resistant (CR)	46mm
20mm	410, 415	Continuous Thread (CT)	38mm
22mm	400, 405	Continuous Thread (CT)	46mm
22mm	400	Child Resistant (CR)	46mm
24mm	400, 405	Continuous Thread (CT)	46mm
24mm	400	Child Resistant (CR)	50mm
24mm	410, 414, 415	Continuous Thread (CT)	46mm
28mm	400, 405	Continuous Thread (CT)	50mm
28mm	400	Child Resistant (CR)	66mm
28mm	410, 415	Continuous Thread (CT)	50mm
33mm	400, 405	Continuous Thread (CT)	66mm
33mm	400	Child Resistant (CR)	77mm
38mm	400, 405, 2000	Continuous Thread (CT), Lug	66mm
38mm	400	Child Resistant (CR)	77mm
38mm	430	Continuous Thread (CT)	90mm
43mm	400, 405, 2010, 2030	Continuous Thread (CT), Lug	90mm
43mm	485	Continuous Thread (CT)	90mm
45mm	400, 405	Continuous Thread (CT)	90mm
45mm	400	Child Resistant (CR)	90mm
48mm	400, 405, 2030	Continuous Thread (CT), Lug	90mm
48mm	485	Continuous Thread (CT)	105mm
53mm	400, 405, 2030	Continuous Thread (CT), Lug	90mm
53mm	400	Child Resistant (CR)	115mm
53mm	485	Continuous Thread (CT)	115mm
58mm	400, 405, 2030	Continuous Thread (CT), Lug	115mm
63mm	400, 405, 2030	Continuous Thread (CT), Lug	115mm
63mm	485	Buttress	115mm
70mm	400, 405, 2030	Continuous Thread (CT), Lug	115mm
70mm	450, 2035	Continuous Thread (CT), Lug	115mm
82mm	2020, 2040	Lug	145mm
83mm	400, 405	Continuous Thread (CT)	145mm
89mm	400, 405	Continuous Thread (CT)	145mm
100mm	400, 405	Continuous Thread (CT)	165mm
110mm	400, 405	Continuous Thread (CT)	165mm
120mm	400, 405	Continuous Thread (CT)	165mm