

NEW PRODUCT RELEASE

"Always at Your Service"

September 2015

NEW 120 Gallon Double Wall TankDW0120-36

Our newest tank is a freestanding double wall vertical tank with a flat bottom for indoor or outdoor stationary applications. Double wall construction provides containment in the event the inner or primary tank is compromised. An EPDM elastic seal is standard and seals the primary tank to the secondary tank to prevent dirt and moisture from entering the containment space between tanks.

FEATURES:

- Furnished with a 16" vented lid assembly as standard.
- Three fitting flats are provided on the top for custom tank plumbing.
- A 1" service fitting is provided on the secondary tank in the event that the containment requires evacuation.
- Tanks manufactured from linear low density polyethylene with U.V. stabilizers.
- · Standard colors are white, yellow, and black. Consult factory for optional colors.
- Designed for the containment of all chemicals rated for contact with polyethylene. Standard weight tank is designed
 for chemicals with a specific gravity of 1.7. Consult the Application Guideline Manual for known compatible chemicals
 and service temperatures. FDA compliant materials are available.



Overall Tank Dimensions: 36" x 50". Shipping weight of tank is 81 lbs.

Tank UPC: 768570-441172

OPTIONAL FEATURE:

Furnished with a 2" polypropylene fitting with santoprene gasket and 316 stainless steel compression rings. Note that optional fitting must be factory installed. Accessory not sold separately. Consult factory regarding fitting and gasket options.

SPECIFICATIONS:

Optional 2" Fitting - UPC: 768570-195631



Shown with optional fitting

CONTACT US TODAY! (800) 342.3408

sales@denhartogindustries.com







Patent Pending