



ACTUAL SIZE

NOTES :

1. TORQUE SPEC. - TIGHTENING FORCE 8-12 FT. LBS
2. SURFACE FINISH - SPE-SPI # 3
3. MATERIAL - LOW DENSITY POLYETHYLENE
4. COLOR - AS ORDERED
5. HOLE SIZES AVAILABLE -.020, .030, .055, .090, OR NO HOLE AS SHOWN
6. THREAD SPEC. - YORKER BUTTRUSS FORM (1/4 TURNS OF FULL THD.)

REV. LET.	DATE	DESCRIPTION
A	8-14-95	.785 ±.007 WAS .791/.388 ±.008 WAS .377
A	10-15-92	.377 WAS .370 / TORQUE WAS 12 FT LBS ADDED .255 DIA.

  

QTY REQD PER ASST	
DIMENSIONS IN INCHES	
TOLERANCES UNLESS OTHERWISE SPECIFIED:	
2 PL DEC ± .015	
3 PL DEC ± .010	
4 PL DEC ± .010	
ANGLES ± 1/2°	
SURF TEXTURE	
REMOVE BURNS, BREAK SPONGE EDGES, OTHER MAX	

  

MATERIAL	SEE NOTE 2
DR. T.O.S.	CUSTOMER
CHG. N.M.V.	11-6-92
PART NAME NUMBER	SPOUT CAP 120 MM 400 FINISH
SCALE	AS NOTED
BALL UNIFORM HOLD NUMBER	
SHEET	1 OF 1
REV	B

