



- NOTES:
- 1 7" ACCESS W/ THREADED LID AND RIM
 - 2 MOLDED IN PUMP SHELF
 - 3 PRIMARY CALCULATED GALLONS PER INCH: 1,721 GPI
 - 4 CALCULATED STRAIGHT SIDE CAPACITY: 65,085 GAL.
 - 5 SECONDARY CALCULATED GALLONS PER INCH: 2,233 GPI
 - 6 CALCULATED STRAIGHT SIDE CAPACITY: 84,977 GAL.

ACCESSORIES			
MK	SIZE	DESCRIPTION	DEG ELEV DOME

REV	REVISION DESCRIPTION	REV DATE
	N/A	

Assmann
CORPORATION OF AMERICA

3000 N TAYLOR ROAD
GARRETT, IN 46738
PHONE: (260) 357-3181
FAX: (260) 357-3738

CUSTOMER APPROVAL

APPROVED BY: _____
DATE: _____

PRIMARY VESSEL	SPECIFIC GRAVITY	TANK WEIGHT	SP.G. MAX	SECONDARY VESSEL	SPECIFIC GRAVITY	TANK WEIGHT	SP.G. MAX
POLYETHYLENE	-	- LBS.	-	POLYETHYLENE	-	-	- LBS.

TITLE: IMT 65 GAL.
DOUBLE WALL STORAGE TANK
ASSMANN CORPORATION OF AMERICA

DWG NUMBER: IMT 65
REV: -

ISSUED BY: D. MYERS
DATE: 10/22/03

ALL DIMENSIONS ARE IN INCHES AND ARE ±3%