

- SERVICE PRESSURE: ATMOSPHERIC
- NSF/ANSI STANDARD 61 CERTIFIED AVAILABLE W/FRP WRAP
- CONTACT CUSTOMER SERVICE FOR MORE INFO

	TOLERANCES: ±1/4" ANGULAR: ± .5° ONE PLACE DECIMAL: ± .25 TWO PLACE DECIMAL: ± .125 THREE PLACE DECIMAL: ± .063 TANK MATERIAL: LLDPE	DRAWN	AAF	08/14/18			enginee	ring	
		CHECKED			PROJEC	PROJECT: PROCHEM® TANKS			
		ENG APPR.			CUSTOM	CUSTOMER: PEABODY STANDARD			
		MFG APPR.			SITE/LOC	SITE/LOCATION: FOB: CORONA, CA			
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PEABODY ENGINEERING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PEABODY ENGINEERING IS PROHIBITED.	INNER TANK S/N:	Q.A.			SALES ORDER:				
	OUTER TANK S/N:	-			SIZE	DESC.			REV.
	CUSTOMER PO#				В	1	1000 GAL PROCHEM® TANK, Ø72.5" x 68"		-
	DO NOT SCALE DRAWING				SCA	LE: 1:22		SHEET	1 OF 1

THE FOLLOWING DRAWINGS ARE CONCEPTUAL AND INTENDED FOR CLIENT REVIEW AND APPROVAL PURPOSES ONLY. THE DRAWINGS ARE AN ESTIMATION OF DESIGN INTENT. FINAL DESIGN, SUPPORTS AND FABRICATION METHODS SHALL BE DETERMINED UPON PRODUCT WILL SATISFY CONCEPTUAL DESIGN INTENT. AND FUNCTION ADEQUATELY AS FABRICATED.