



# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 05/22/2015

Supersedes: 11/03/2011

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : PLASTI DIP CLEAR

Product code : 10109

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Plasti Dip International, Inc.  
3920 Pheasant Ridge Drive  
Blaine, MN 55449  
Phone - (763) 785-2156  
Website: plastidip.com

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (US); 703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Skin Sens. 1 H317  
Muta. 1B H340  
Carc. 1B H350  
Repr. 2 H361  
STOT SE 3 H336  
STOT RE 2 H373  
Asp. Tox. 1 H304  
Carc. 2 H351

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02



GHS07



GHS08

Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H336 - May cause drowsiness or dizziness  
H340 - May cause genetic defects  
H350 - May cause cancer  
H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe mist, vapours, fume  
P261 - Avoid breathing vapours, mist, fume  
P264 - Wash hands, forearms and face thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear eye protection, face protection, protective clothing, protective gloves  
P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER  
P302+P352 - If on skin: Wash with plenty of water  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention  
P312 - Call a doctor, a POISON CENTER if you feel unwell  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work on this label)  
P331 - Do NOT induce vomiting  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to licensed waste handling facility

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Solvent naphtha, petroleum, light aliphatic	(CAS No) 64742-89-8	15 - 40
Naphtha, petroleum, hydrotreated light	(CAS No) 64742-49-0	15 - 40
Toluene	(CAS No) 108-88-3	10 - 30
Hexane	(CAS No) 110-54-3	10 - 30
Limestone	(CAS No) 1317-65-3	5.74
Silica, amorphous, fumed, crystalline-free	(CAS No) 112945-52-5	1 - 5
3-Methylpentane	(CAS No) 96-14-0	1 - 5
Methylcyclopentane	(CAS No) 96-37-7	1 - 5
Methyl ethyl ketone	(CAS No) 78-93-3	1 - 5
n-Heptane	(CAS No) 142-82-5	1 - 5
Octane	(CAS No) 111-65-9	1 - 5
2-Methylpentane	(CAS No) 107-83-5	0.1 - 1
Ethylbenzene	(CAS No) 100-41-4	0.1 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS No) 41556-26-7	0.1 - 1
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidyl ester	(CAS No) 82919-37-7	0.1 - 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.

First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.

First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.

First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. . May cause damage to organs through prolonged or repeated exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray. Sand.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: Heating may cause an explosion.
Reactivity	: No dangerous reactions known under normal conditions of use.

### 5.3. Advice for firefighters

Precautionary measures fire	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus and protective suit (see item 8).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear Protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.
----------------------	---

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Exclude sources of ignition and ventilate the area. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

### 6.4. Reference to other sections

See Sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep away from sources of ignition - No smoking.
-------------------------------	---

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep the container tightly closed. Store in a dry, cool and well-ventilated place. Keep away from ignition sources.
Storage temperature	: Do not store above 49 °C (120 °F)

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Toluene (108-88-3)</b>	
ACGIH TWA (ppm)	20
Remark (ACGIH)	Visual impair; female repro;
<b>Hexane (110-54-3)</b>	
ACGIH TWA (ppm)	50
OSHA PEL (TWA) (mg/m³)	1800
OSHA PEL (TWA) (ppm)	500
<b>3-Methylpentane (96-14-0)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Methylcyclopentane (96-37-7)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>2-Methylpentane (107-83-5)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Methyl ethyl ketone (78-93-3)</b>	
ACGIH TWA (ppm)	200
ACGIH STEL (ppm)	300
OSHA PEL (TWA) (mg/m³)	590
OSHA PEL (TWA) (ppm)	200
OSHA PEL (STEL) (mg/m³)	885
OSHA PEL (STEL) (ppm)	300
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidiny ester (82919-37-7)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Limestone (1317-65-3)</b>	
Remark (ACGIH)	OELs not established
OSHA PEL (TWA) (mg/m³)	5 respirable fraction
<b>Silica: Crystalline, quartz (14808-60-7)</b>	
ACGIH TWA (mg/m³)	0.025 (respirable fraction)
OSHA PEL (TWA) (mg/m³)	(30)/(%SiO2 + 2) total dust; (10)/(%SiO2 + 2) respirable fraction
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Octane (111-65-9)</b>	
ACGIH TWA (ppm)	300
OSHA PEL (TWA) (mg/m³)	2350
OSHA PEL (TWA) (ppm)	500

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>n-Heptane (142-82-5)</b>	
ACGIH TWA (ppm)	400
ACGIH STEL (ppm)	500 (listed under Heptane, all isomers)
OSHA PEL (TWA) (mg/m³)	2000
OSHA PEL (TWA) (ppm)	500
OSHA PEL (STEL) (mg/m³)	2000
OSHA PEL (STEL) (ppm)	500
<b>Ethylbenzene (100-41-4)</b>	
ACGIH TWA (ppm)	20
Remark (ACGIH)	upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment
OSHA PEL (TWA) (mg/m³)	435
OSHA PEL (TWA) (ppm)	100
OSHA PEL (STEL) (mg/m³)	545
OSHA PEL (STEL) (ppm)	125

### 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Change contaminated gloves immediately. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection

: Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Honey Like Substance.
Color	: Various.
Odor	: characteristic.
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: > 1
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 65 - 141 °C (149 - 285 °F)
Flash point	: -23 °C (-10 °F) (TCC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapour pressure	: 125 mm Hg (20 °C)
Relative vapour density at 20 °C	: (Heavier than Air)
Relative density	: 0.79 - 0.83 (H <sub>2</sub> O = 1)
Solubility	: Water: Insoluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.9 - 11.5 vol %

### 9.2. Other information

VOC content	: 72 - 75 %
-------------	-------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Ignition sources. Heat. Sparks. Open flame. Static electricity.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Alkali metals. Halogens.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

<b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>	
LD50 oral rat	5000 mg/kg mouse
LD50 dermal rabbit	3000 mg/kg
<b>Toluene (108-88-3)</b>	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
<b>Hexane (110-54-3)</b>	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (ppm)	48000 ppm/4h
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>	
LD50 oral rat	2615 mg/kg
<b>Silica: Crystalline, quartz (14808-60-7)</b>	
LD50 oral rat	500 mg/kg
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	73680 ppm/4h
<b>Octane (111-65-9)</b>	
LC50 inhalation rat (mg/l)	118 g/m <sup>3</sup> 4 h
<b>n-Heptane (142-82-5)</b>	
LD50 oral rat	5000 mg/kg
LD50 dermal rabbit	3000 mg/kg

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>n-Heptane (142-82-5)</b>	
LC50 inhalation rat (mg/l)	103 g/m³ 4h
<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects. Not classified.
Carcinogenicity	: May cause cancer. Suspected of causing cancer.
<b>Silica: Crystalline, quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans
<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. . May cause damage to organs through prolonged or repeated exposure.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : No information available.

<b>Hexane (110-54-3)</b>	
LC50 fishes 1	2.1 - 2.98 mg/l 96 Hr LC50 Pimephales promelas [flow-through]

### 12.2. Persistence and degradability

<b>PLASTI DIP F698, F819, F820</b>	
Persistence and degradability	No information available.

### 12.3. Bioaccumulative potential

<b>PLASTI DIP F698, F819, F820</b>	
Bioaccumulative potential	No information available.

### 12.4. Mobility in soil

<b>PLASTI DIP F698, F819, F820</b>	
Ecology - soil	No information available.

### 12.5. Other adverse effects

Other adverse effects : No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1139 Coating solution (Contains: Hexane; Toluene), 3, II  
UN-No.(DOT) : 1139  
DOT NA no. : UN1139  
Proper Shipping Name (DOT) : Coating solution  
(Contains: Hexane; Toluene)  
Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L  
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

#### Additional information

Other information : No supplementary information available.

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### PLASTI DIP F698, F819, F820

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

SARA Section 311/312 Hazard Classes	
Immediate (acute) health hazard	
Delayed (chronic) health hazard	
Fire hazard	

##### Xylenes (o-, m-, p- isomers) (1330-20-7)

Section 302 (EHS) TPQ

Section 304 EHS RQ

CERCLA RQ

100 lb

Section 313

Listed on US SARA Section 313

##### Ethylbenzene (100-41-4)

Section 302 (EHS) TPQ

Section 304 EHS RQ

CERCLA RQ

1000 lb

Section 313

Listed on US SARA Section 313

##### Acetone (67-64-1)

Section 302 (EHS) TPQ

Section 304 EHS RQ

CERCLA RQ

5000 lb

Section 313

Not Listed on US SARA Section 313

##### Hexane (110-54-3)

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	5000 lb
Section 313	Listed on US SARA Section 313

<b>Antimony oxide (Sb2O3) (1309-64-4)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 313

<b>Arsenic (7440-38-2)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	1 lb
Section 313	Listed on US SARA Section 313

<b>Lead (7439-92-1)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	10 lb
Section 313	Listed on US SARA Section 313

<b>Methyl ethyl ketone (78-93-3)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	5000 lb
Section 313	Not Listed on US SARA Section 313

<b>Toluene (108-88-3)</b>	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 313

### 15.2. International regulations

No additional information available.

### 15.3. US State regulations

#### California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

<b>Toluene (108-88-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	7000b µg/day

<b>Silica: Crystalline, quartz (14808-60-7)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	Not available

# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	54 (inhalation) µg/day 41 (oral) µg/day
<b>Toluene (108-88-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Hexane (110-54-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>3-Methylpentane (96-14-0)</b>				
U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Methylcyclopentane (96-37-7)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>2-Methylpentane (107-83-5)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Methyl ethyl ketone (78-93-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Limestone (1317-65-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Silica: Crystalline, quartz (14808-60-7)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List				
<b>Octane (111-65-9)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>n-Heptane (142-82-5)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Ethylbenzene (100-41-4)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				

### SECTION 16: Other information

Indication of changes	: Revision 1.0: New SDS Created.
Revision date	: 05/22/2015
Other information	: Author: BCS.


# PLASTI DIP CLEAR

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



### HMIS III Rating

Health	: 3*
Flammability	: 4
Physical	: 1
Personal Protection	:

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product