

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 11/25/2015 Version: 1.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

: HCF Black : Mixture : 30103

#### 1.1. Product identifier

| Product name |  |  |
|--------------|--|--|
| Product form |  |  |
| Product code |  |  |

1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Details of the supplier of the safety data sheet 1.3.

Plasti Dip International, Inc. 3920 Pheasant Ridge Drive Blaine, MN 55449 Phone - (763) 785-2156

#### 1.4. Emergency telephone number

Emergency number

: CHEMTREC: 1-800-424-9300 (US); 703-527-3887 (International)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## **GHS-US** classification

Flam. Lig. 4 H227 Skin Sens. 1 H317 H351 Carc. 2 STOT RE 2 H373

#### 2.2. Label elements

#### **GHS-US** labelling

Hazard pictograms (GHS-US)



Signal word (GHS-US) Hazard statements (GHS-US)

Precautionary statements (GHS-US)

## : Warning

- H227 Combustible liquid
  - H317 May cause an allergic skin reaction
  - H351 Suspected of causing cancer
  - H373 May cause damage to organs through prolonged or repeated exposure
  - P201 Obtain special instructions before use
  - P202 Do not handle until all safety precautions have been read and understood
  - P210 Keep away from heat, hot surfaces, open flames, sparks. No smoking
  - P260 Do not breathe vapours, mist
  - P261 Avoid breathing vapours, mist
  - P272 Contaminated work clothing must not be allowed out of the workplace
- P280 Wear eye protection, protective clothing, protective gloves
- P302+P352 If on skin: Wash with plenty of soap and water
- P308+P313 If exposed or concerned: Get medical advice/attention
- P314 Get medical advice/attention if you feel unwell
- P321 Specific treatment (see first aid instructions on this label)
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention
- P363 Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use carbon dioxide (CO2), foam, dry extinguishing powder to extinauish

- P403+P235 Store in a well-ventilated place. Keep cool
- P405 Store locked up
- P501 Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

No additional information available

#### Unknown acute toxicity (GHS-US) 2.4

No data available

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

| Name   | Product identifier  | %       |
|--|---------------------|---------|
| Kaolin   | (CAS No) 1332-58-7  | 5 - 10  |
| 2-Butoxyethanol  | (CAS No) 111-76-2   | 3 - 7   |
| Titanium dioxide   | (CAS No) 13463-67-7 | 0.1 - 1 |
| Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl-<br>with 2-methyl-3(2H)-isothiazolone | (CAS No) 55965-84-9 | <= 0.1  |

## **SECTION 4: First aid measures**

| 4.1. Description of first aid measures |   |
|--|---|
| First-aid measures general             | : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.                         |
| First-aid measures after inhalation    | : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.   |
| First-aid measures after skin contact  | : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.   |
| First-aid measures after eye contact   | : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing. |
| First-aid measures after ingestion     | : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.   |
| 4.2. Most important symptoms and effe  | ts, both acute and delayed  |
| Symptoms/injuries                      | : May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to<br>organs through prolonged or repeated exposure.   |
| Symptoms/injuries after inhalation     | : May cause respiratory irritation.   |
| Symptoms/injuries after skin contact   | : Causes skin irritation. May cause an allergic skin reaction.  |
| Symptoms/injuries after eye contact    | : Direct contact with the eyes is likely to be irritating.  |
| Symptoms/injuries after ingestion      | : May cause gastrointestinal irritation.  |
| Chronic symptoms                       | : Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.   |

#### Indication of any immediate medical attention and special treatment needed 4.3.

No additional information available

| SECT     | SECTION 5: Firefighting measures  |  |  |
|----------|---|--|--|
| 5.1.     | Extinguishing media   |  |  |
| Suitable | e extinguishing media   | : Carbon dioxide. Foam. Dry chemical.  |  |
| 5.2.     | Special hazards arising from the s  | ubstance or mixture  |  |
| Fire haz | zard  | : Combustible liquid.  |  |
| Explosi  | on hazard   | : Product is not explosive.  |  |
| Reactiv  | ity   | : No dangerous reactions known under normal conditions of use.   |  |
| 5.3.     | Advice for firefighters   |  |  |
| Firefigh | ting instructions   | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion. Avoid contact with sprayed water - material slippery when wet. |  |
| Protecti | Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protective Self-contained breathing apparatus.   |  |  |
| Other in | Other information : Material can splatter above 100 °C / 212 °F.  |  |  |
| SECT     | ION 6: Accidental release me  | asures   |  |
| 6.1.     | I. Personal precautions, protective equipment and emergency procedures  |  |  |
| Genera   | General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-uproperly equipped with respiratory equipment and full chemical protective gear (see Section 2014). |  |  |
| 6.1.1.   | For non-emergency personnel   |  |  |
| Protecti | Protective equipment : Wear Protective equipment as described in Section 8.   |  |  |
|          |   |  |  |

## Safety Data Sheet

| Emergen              | cy procedures   | :        | : Evacuate unnecessary personnel.  |  |  |
|----------------------|---|----------|--|--|--|
| 6.1.2.               | For emergency responders                                |          |  |  |  |
| Protective equipment |   |          | Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.  |  |  |
| 6.2.                 | Environmental precautions                               |          |  |  |  |
| Prevent e            | entry to sewers and public waters. N                    | otify au | thorities if liquid enters sewers or public waters. Avoid release to the environment.  |  |  |
| 6.3.                 | 3. Methods and material for containment and cleaning up |          | and cleaning up  |  |  |
| For conta            | inment  |          | Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.  |  |  |
| Methods              | for cleaning up   |          | Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Sweep<br>or shovel spills into appropriate container for disposal. This material and its container must be<br>disposed of in a safe way, and as per local legislation. |  |  |
| 6.4.                 | Reference to other sections                             |          |  |  |  |
| No additi            | onal information available                              |          |  |  |  |

# 7.1. Precautions for safe handling Precautions for safe handling : Handle in accordance with good industrial hygiene and safety procedures. Do not handle until all safety precautions have been read and understood. Use only in well-ventilated areas. Do not breathe mist, vapours. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep from freezing.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

| Mixture, 3(2H)-isothiazolone, 5-chloro-2-methyl- with 2-methyl- with 2-methyl-3(2H)-isothiazolone (55965-<br>84-9) |  |  |
|--|--|--|
| Remark (ACGIH) OELs not established  |  |  |
| Remark (OSHA)  | OELs not established   |  |
| Kaolin (1332-58-7)   |  |  |
| ACGIH TWA (mg/m³)  | 2 (particulate matter containing no asbestos and < 1% crystalline silica, respirable fraction) |  |
| Remark (ACGIH)   | Pneumoconiosis   |  |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 15 (toal dust) 5 (respirable fraction)   |  |
| 2-Butoxyethanol (111-76-2)   |  |  |
| ACGIH TWA (ppm)  | 20 ppm   |  |
| Remark (ACGIH) eye and upper respiratory tract irritation  |  |  |
| OSHA PEL (TWA) (mg/m³)   | 240 mg/m³  |  |
| OSHA PEL (TWA) (ppm)   | 50 ppm   |  |
| Titanium dioxide (13463-67-7)  |  |  |
| ACGIH TWA (mg/m <sup>3</sup> )   | 10   |  |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 15 total dust  |  |

#### 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Gloves. Protective goggles. Protective clothing.



## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Hand protection          | : Use gloves chemically resistant to this material when prolonged or repeated contact could<br>occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove<br>materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate,<br>PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove<br>supplier. |
|--------------------------|--|
| Eye protection           | : Wear eye protection, including chemical splash goggles and a face shield when possibility<br>exists for eye contact due to spraying liquid or airborne particles.  |
| Skin and body protection | : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.  |
| Respiratory protection   | <ul> <li>Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or<br/>other applicable OELs, use NIOSH-approved respiratory protective equipment.</li> </ul>  |

## **SECTION 9: Physical and chemical properties**

| 9.1. Information on basic physical and chemical properties |                                  |
|--|----------------------------------|
| Physical state   | : Liquid                         |
| Appearance   | : Syrupy liquid.                 |
| Color  | : Black.                         |
| Odor   | : Slight. Ammonia-like.          |
| Odor Threshold   | : No data available              |
| рН   | : No data available              |
| Relative evaporation rate (butylacetate=1)                 | : <1                             |
| Melting point  | : No data available              |
| Freezing point   | : No data available              |
| Boiling point  | : 100 °C (212 °F)                |
| Flash point  | : 67 °C (152.6 °F)               |
| Auto-ignition temperature                                  | : No data available              |
| Decomposition temperature                                  | : No data available              |
| Flammability (solid, gas)                                  | : No data available              |
| Vapour pressure  | : 17.5 mm Hg @ 20 °C (68 °F)     |
| Relative vapour density at 20 °C                           | : < 1 (Air = 1)                  |
| Relative density   | : 1 - 1.1 (H <sub>2</sub> O = 1) |
| Solubility   | : Insoluble in water.            |
| Log Pow  | : No data available              |
| Log Kow  | : No data available              |
| Viscosity, kinematic                                       | : No data available              |
| Viscosity, dynamic   | : No data available              |
| Explosive properties                                       | : No data available              |
| Oxidising properties                                       | : No data available              |
| Explosive limits   | : No data available              |
| 9.2. Other information                                     |                                  |
| VOC content  | : 5.1 % (0.5 VOC LBS./GAL)       |

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

None known.

## 10.5. Incompatible materials

Oxidizing agent.

#### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Prepared according to Federal Register / Vol. //, No. 58 /                |  |
|---|--|
| SECTION 11: Toxicological informati                                       | on   |
| 11.1. Information on toxicological effects                                |  |
| Acute toxicity  | : Not classified   |
| Skin corrosion/irritation   | : Not classified.  |
| Serious eye damage/irritation   | : Not classified.  |
| Respiratory or skin sensitisation   | : May cause an allergic skin reaction.   |
| Germ cell mutagenicity  | : Not classified   |
| Carcinogenicity   | : Suspected of causing cancer.   |
| Titanium dioxide (13463-67-7)   |  |
| IARC group  | 2B - Possibly carcinogenic to humans   |
| Ethyl acrylate (140-88-5)   |  |
| IARC group  | 2B - Possibly carcinogenic to humans   |
| Carbon black (1333-86-4)  |  |
| IARC group  | 2B - Possibly carcinogenic to humans   |
| - ·   |  |
| Reproductive toxicity<br>Specific target organ toxicity (single exposure) | : Not classified<br>: Not classified   |
|   |  |
| Specific target organ toxicity (repeated exposure)                        | : May cause damage to organs through prolonged or repeated exposure.   |
| Aspiration hazard   | : Not classified   |
| Symptoms/injuries after inhalation  | : May cause respiratory irritation.  |
| Symptoms/injuries after skin contact                                      | : Causes skin irritation. May cause an allergic skin reaction.   |
| Symptoms/injuries after eye contact                                       | : Direct contact with the eyes is likely to be irritating.   |
| Symptoms/injuries after ingestion   | : May cause gastrointestinal irritation.   |
| Chronic symptoms  | : Suspected of causing cancer. May cause damage to organs through prolonged or repeated  |
|   | exposure.  |
| SECTION 12: Ecological information  |  |
| 12.1. Toxicity  |  |
| Ecology - general   | : No information available.  |
|   |  |
| 12.2. Persistence and degradability                                       |  |
| HCF Black   |  |
| Persistence and degradability   | No information available.  |
| 12.3. Bioaccumulative potential   |  |
| HCF Black   |  |
| Bioaccumulative potential   | No information available.  |
| 12.4. Mobility in soil  |  |
| HCF Black   |  |
| Ecology - soil  | No information available.  |
| <b>12.5.</b> Other adverse effects<br>No additional information available |  |
| SECTION 13: Disposal consideration  | s  |
| 13.1. Waste treatment methods   |  |
| Waste treatment methods   | : Do not discharge to public wastewater systems without permit of pollution control authorities.<br>No discharge to surface waters is allowed without an NPDES permit. |
| Waste disposal recommendations  | : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.                                |
| SECTION 14: Transport information   |  |
| In accordance with DOT  |  |
|   |  |
| Not hazardous for transport Additional information                        |  |
|   |  |
| Other information   | : No supplementary information available.  |
| Transport by sea<br>No additional information available                   |  |
|   |  |
| 14/05/0045  |  |

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Air transport

No additional information available

| SECTION 15: Regulatory information                               | on  |
|--|---|
| 5.1. US Federal regulations                                      |   |
| HCF Black  |   |
| All chemical substances in this product are lis<br>or are exempt | sted in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory |
| SARA Section 311/312 Hazard Classes                              | Immediate (acute) health hazard<br>Delayed (chronic) health hazard                            |
| Ammonium hydroxide (1336-21-6)                                   |   |
| Section 302 (EHS) TPQ  |   |
| Section 304 EHS RQ   |   |
| CERCLA RQ  | 1000 lb   |
| Section 313  | Listed on US SARA Section 313   |
| 2-Butoxyethanol (111-76-2)                                       |   |
| Section 302 (EHS) TPQ  | Certain glycol ethers   |
| Section 304 EHS RQ   | Certain glycol ethers   |
| CERCLA RQ  | Certain glycol ethers   |
| Section 313  | Listed on US SARA Section 313   |

## 15.2. International regulations

No additional information available.

#### 15.3. US State regulations

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

| Titanium dioxide (1346  | 63-67-7)   |   |   |                                      |
|---|--|---|---|--------------------------------------|
| U.S California -<br>Proposition 65 -<br>Carcinogens List              | U.S California -<br>Proposition 65 -<br>Developmental Toxicity | U.S California -<br>Proposition 65 -<br>Reproductive Toxicity -<br>Female | U.S California -<br>Proposition 65 -<br>Reproductive Toxicity -<br>Male | Non-significant<br>risk level (NSRL) |
| Yes   | No   | No  | No  | Not available                        |
| Ethyl acrylate (140-88-   | 5)   |   |   |                                      |
| U.S California -<br>Proposition 65 -<br>Carcinogens List              | U.S California -<br>Proposition 65 -<br>Developmental Toxicity | U.S California -<br>Proposition 65 -<br>Reproductive Toxicity -<br>Female | U.S California -<br>Proposition 65 -<br>Reproductive Toxicity -<br>Male | Non-significant<br>risk level (NSRL) |
| Yes   | No   | No  | No  | Not available                        |
| Carbon black (1333-86   | -4)  |   |   |                                      |
| U.S California -<br>Proposition 65 -<br>Carcinogens List              | U.S California -<br>Proposition 65 -<br>Developmental Toxicity | U.S California -<br>Proposition 65 -<br>Reproductive Toxicity -<br>Female | U.S California -<br>Proposition 65 -<br>Reproductive Toxicity -<br>Male | Non-significant<br>risk level (NSRL) |
| Yes   | No   | No  | No  | Not available                        |
| Kaolin (1332-58-7)  |  |   | •   |                                      |
| U.S New Jersey - Rig<br>U.S Pennsylvania - R<br>U.S Massachusetts - I |  | List  |   |                                      |
| Titonium dioxido (1246  | 2 CZ Z)  |   |   |                                      |

| Titanium dioxide (13463-67-7)   |
|---|
| U.S Massachusetts - Right To Know List<br>U.S New Jersey - Right to Know Hazardous Substance List |
| U.S Pennsylvania - RTK (Right to Know) List   |
| 2-Butoxyethanol (111-76-2)  |
| U.S Massachusetts - Right To Know List  |
| LLO New Jensey, Diabities Manuel Lensedeux Outertenses List                                       |

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Safety Data Sheet Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| SECTION 16: Other information |   |
|-------------------------------|---|
| Indication of changes         | : Revision 1.0: New SDS Created.  |
| Revision date                 | : 11/25/2015  |
| Other information             | : Author: BCS.  |
| NFPA health hazard            | : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. |
| NFPA fire hazard              | : 1 - Must be preheated before ignition can occur.  |
| NFPA reactivity               | : 0 - Normally stable, even under fire exposure conditions,<br>and are not reactive with water.                       |
| HMIS III Rating               |   |
| Health                        | : 3*  |
| Flammability                  | : 1   |
| Physical                      | : 0   |
| Personal Protection           | :   |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product