

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Plasti Dip UV Red  
 Product form : Mixture  
 Product code : 10101UV

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Plasti Dip International, Inc.  
 3920 Pheasant Ridge Drive  
 Blaine, MN 55449  
 Phone - (763) 785-2156

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (US); 703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 2 H225  
 Skin Irrit. 2 H315  
 Skin Sens. 1 H317  
 Carc. 2 H351  
 Repr. 2 H361  
 STOT SE 3 H336  
 STOT RE 1 H372  
 Asp. Tox. 1 H304

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02



GHS07



GHS08

Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour  
 H304 - May be fatal if swallowed and enters airways  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H336 - May cause drowsiness or dizziness  
 H351 - Suspected of causing cancer  
 H361 - Suspected of damaging fertility or the unborn child  
 H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
 P202 - Do not handle until all safety precautions have been read and understood  
 P210 - Keep away from sparks, open flames, heat. - No smoking  
 P233 - Keep container tightly closed  
 P240 - Ground/bond container and receiving equipment  
 P241 - Use explosion-proof ventilating, lighting, electrical equipment  
 P242 - Use only non-sparking tools  
 P243 - Take precautionary measures against static discharge  
 P260 - Do not breathe vapours, mist  
 P264 - Wash hands, forearms and face thoroughly after handling  
 P270 - Do not eat, drink or smoke when using this product  
 P271 - Use only outdoors or in a well-ventilated area  
 P272 - Contaminated work clothing must not be allowed out of the workplace  
 P280 - Wear protective gloves, eye protection, protective clothing  
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor  
 P302+P352 - If on skin: Wash with plenty of soap and water  
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
 P308+P313 - If exposed or concerned: Get medical advice/attention  
 P312 - Call a POISON CENTER, a doctor if you feel unwell

# Plasti Dip UV Red

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see first aid instructions on this label)  
P331 - Do NOT induce vomiting  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish  
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Distillates, petroleum, light distillate hydrotreating process, low-boiling	(CAS No) 68410-97-9	15 - 40
Toluene	(CAS No) 108-88-3	10 - 30
Hexane	(CAS No) 110-54-3	7 - 13
3-Methylpentane	(CAS No) 96-14-0	1 - 5
Methylcyclopentane	(CAS No) 96-37-7	1 - 5
Methyl ethyl ketone	(CAS No) 78-93-3	1 - 5
Stoddard solvent	(CAS No) 8052-41-3	0.1 - 1
Methyl ethyl ketoxime	(CAS No) 96-29-7	<= 0.1
Titanium dioxide	(CAS No) 13463-67-7	<= 0.1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
First-aid measures after skin contact	: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
First-aid measures after eye contact	: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

# Plasti Dip UV Red

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Carbon dioxide. Dry chemical.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : Heating may cause an explosion.

Reactivity : No dangerous reactions known under normal conditions of use.

#### 5.3. Advice for firefighters

Precautionary measures fire : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : This material is flammable and may be ignited by heat, sparks, or static electricity.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ventilate area. Keep upwind. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Prevent entry to sewers and public waters.

Methods for cleaning up : Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This material and its container must be disposed of in a safe way, and as per local legislation.

#### 6.4. Reference to other sections

See Sections 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Handle in accordance with good industrial hygiene and safety procedures. Use only in well-ventilated areas. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Keep away from sources of ignition - No smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep the container tightly closed. Store in a dry, cool and well-ventilated place. Keep away from ignition sources.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
Hexane (110-54-3)	
ACGIH TWA (ppm)	50
OSHA PEL (TWA) (mg/m³)	1800
OSHA PEL (TWA) (ppm)	500

# Plasti Dip UV Red

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>3-Methylpentane (96-14-0)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Methylcyclopentane (96-37-7)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Toluene (108-88-3)</b>	
ACGIH TWA (ppm)	20
Remark (ACGIH)	Visual impair; female repro;
<b>Methyl ethyl ketone (78-93-3)</b>	
ACGIH TWA (ppm)	200
ACGIH STEL (ppm)	300
OSHA PEL (TWA) (mg/m³)	590
OSHA PEL (TWA) (ppm)	200
OSHA PEL (STEL) (mg/m³)	885
OSHA PEL (STEL) (ppm)	300
<b>Stoddard solvent (8052-41-3)</b>	
ACGIH TWA (ppm)	100
Remark (ACGIH)	CNS impairment; Eye, skin, and kidney damage; nausea
OSHA PEL (TWA) (mg/m³)	2900
OSHA PEL (TWA) (ppm)	500
<b>Titanium dioxide (13463-67-7)</b>	
ACGIH TWA (mg/m³)	10
OSHA PEL (TWA) (mg/m³)	15 total dust
<b>Methyl ethyl ketoxime (96-29-7)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

### 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Protective goggles. Wear chemically impervious apron over labcoat and full coverage clothing. Insufficient ventilation: wear respiratory protection.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection

: Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Red.

# Plasti Dip UV Red

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Ignition sources. Heat. Sparks. Open flame. Static electricity.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

None known.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.

<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>Benzene (71-43-2)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

# Plasti Dip UV Red

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Silica: Crystalline, quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : No information available.

Hexane (110-54-3)	
LC50 fish 1	2.1 - 2.98 mg/l 96 Hr LC50 Pimephales promelas [flow-through]

#### 12.2. Persistence and degradability

Plasti Dip UV Red	
Persistence and degradability	No information available.

#### 12.3. Bioaccumulative potential

Plasti Dip UV Red	
Bioaccumulative potential	No information available.

#### 12.4. Mobility in soil

Plasti Dip UV Red	
Ecology - soil	No information available.

#### 12.5. Other adverse effects

Other adverse effects : No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1139 Coating solution (Contains: Toluene, Hexane, Methyl ethyl ketone), 3, II

UN-No.(DOT) : 1139

DOT NA no. : UN1139

Proper Shipping Name (DOT) : Coating solution  
Contains: Toluene, Hexane, Methyl ethyl ketone

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Quantity Limitations Passenger aircraft/rail : 5 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)

# Plasti Dip UV Red

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

### Additional information

Other information : No supplementary information available.

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Plasti Dip UV Red	
All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory or are exempt	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard

Toluene (108-88-3)	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 313

Methyl ethyl ketone (78-93-3)	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	5000 lb
Section 313	Not Listed on US SARA Section 313

Hexane (110-54-3)	
Section 302 (EHS) TPQ	
Section 304 EHS RQ	
CERCLA RQ	5000 lb
Section 313	Listed on US SARA Section 313

### 15.2. International regulations

No additional information available.

### 15.3. US State regulations

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Toluene (108-88-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Maximum allowable dose level (MADL)
No	Yes	No	No	7000 µg/day
Titanium dioxide (13463-67-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	Not available

# Plasti Dip UV Red

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Benzene (71-43-2)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL) Maximum allowable dose level (MADL)
Yes	Yes	No	Yes	13 (inhalation) 6.4 (oral) µg/day 49 (inhalation) 24 (oral) µg/day
<b>Ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	54 (inhalation) 41 (oral) µg/day
<b>Silica: Crystalline, quartz (14808-60-7)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	Not available
<b>Hexane (110-54-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>3-Methylpentane (96-14-0)</b>				
U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Methylcyclopentane (96-37-7)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Toluene (108-88-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Methyl ethyl ketone (78-93-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Stoddard solvent (8052-41-3)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Titanium dioxide (13463-67-7)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>2-Methylpentane (107-83-5)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Benzene (71-43-2)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				



# Plasti Dip UV Red

## Safety Data Sheet


Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Ethylbenzene (100-41-4)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
<b>Limestone (1317-65-3)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Silica: Crystalline, quartz (14808-60-7)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
<b>Due to pigments may contain up to 2 Proprietary Non-Hazardous Ingredients (Proprietary CAS)</b>
U.S. - State Right To Know List

### SECTION 16: Other information

Indication of changes	: Revision 1.0: New SDS Created.
Revision date	: 11/04/2015
Other information	: Author: BCS.

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



#### HMIS III Rating

Health	: 3*
Flammability	: 4
Physical	: 1
Personal Protection	:

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product