



Relates to our
70369

Assembly Instruction for 1100ML TYPE PLUS 32

ALUMINUM BOTTLES U.N. APPROVED AS SINGLE PACKAGINGS (1B1).

This bottle has been tested and approved with the following components:

Option 1 : Certificate 0160 Index 3. Group I, II, III

1/ ALUMINUM BOTTLE

2/ PP CAP WITH ALPE (Aluminum Foil)/PEE LINER

After filling, insert the sealing plug to full depth by pushing it down, screw the cap to the following recommended torque: Between 35 and 44 Inch per lbs.

Recommended capping tool. Item # MCAPR02. Torque is preset at 38 inch per lbs.
Custom chuck. Item # ADAPT32

Option 2 : Extension 001 Index 1 to Certificate 0160. I, II, III

1/ ALUMINUM BOTTLE

2/ LDPE PLUG

3/ PP CAP WITH ALPE (Aluminum Foil)/PEE LINER

After filling, screw the cap to the following recommended torque: Between 22 and 36 Inch per lbs.

Recommended capping tool. Item # MCAPR01. Torque is preset at 29 inch per lbs.
Custom chuck. Item # ADAPT32

Option 3 : Extension 002 Index 0 to Certificate 0160. Group I, II, III

1/ ALUMINUM BOTTLE

2/ PP CAP WITH PTFE (Teflon) LINER

After filling, screw the cap to the following recommended torque: Between 31 and 40 Inch per lbs.

Recommended capping tool. Item # MCAPR02. Torque is preset at 38 inch per lbs.
Custom chuck. Item # ADAPT32

Labeling and marking are the shipper responsibility.

Elemental Container Inc . 860 Springfield Road South . Union, New Jersey 07083 . USA
Telephone 908.687.7720 . 800. 577.7624 . Fax 908.687.5157 . www.aluminumbottles.com
Last update 08/29/12

1 of 2 pgs

Ins. # 75507

ELEMENTAL
CONTAINER 
ALUMINUM PACKAGING

Elemental Container assumes no responsibility for the package integrity or compliance to the U.N. hazardous goods regulations unless all package components are assembled per the above instructions and supplied by Elemental Container.

Product compatibility with the aluminum is the customer responsibility and must be in accordance with the Packaging instructions of the 49CFR. Container compliance is predicated on a product maximum density of 1.2 (H₂O = 1.0).

UN certificates are available upon request.