



THERMAL PRINTER

MODEL DA220

DESKTOP DIRECT THERMAL
PRINTER

PRINTING

- **Printing Method:** Direct Thermal
- **Resolution:** 8 dots/mm (203 dpi)
- **Max. Print Speed:** 152.4mm (6")/second
- **Max. Print Width:** 108mm (4.25")
- **Max. Print Length:** 25,400mm (1000")

HARDWARE

- **Processor:** 32-bit RISC CPU
- **Memory:** 128 MB Flash memory
64 MB DRAM

INTERFACE

- **PCBA1:** USB 2.0 high speed mode, USB Host, RS-232 and Ethernet (standard)
- **PCBA2:** USB 2.0 and Ethernet (factory option)
Internal 802.11 a/b/g/n wireless (factory option)
Internal Bluetooth (factory option)

SENSORS

Transmissive gap sensor
Black mark reflective sensor
Head open sensor

MEDIA

- **Media Type:** Continuous, black mark, fan-fold, notched (outside wound)
- **Media Width:** 19mm — 114mm (0.7" — 4.5")
- **Media Thickness:** 0.055mm — 0.19mm (2.16mil — 7.48mil)
- **Media Core Diameter:** 25.4mm — 38mm (1" — 1.5")
- **Label Roll Capacity:** 127mm (5") O.D.

POWER

- **Power:** External universal switching power supply
- **Input:** AC 100—240V, 2.0A, 50—60Hz
- **Output:** DC 24V, 2.5A, 60W

OPERATION

Operation Switch, Button, LED:
1 power switch, 1 feed button, 1 LED
(3 colors: green, amber & red)

PHYSICAL

- **Enclosure:** Double-walled plastic
- **Physical Dimension:**
172mm (W) × 165mm (H) × 195mm (D)
6.77" (W) × 6.50" (H) × 7.68" (D)
Weight: 1.5kg (3.31lbs)

YOUR LABELS, YOUR SPECIFICATIONS, WHEN YOU NEED IT.

www.Rxlabels.com | orders@exlabels.com | 212 Rxlabels (795-2235)