



ARMOR GUYS

• PROTECTED •

EXTRAFLEX

04-001 SPECIFICATION SHEET

FEATURES:

FIBER
15g, Gray Nylon Liner

COATING
Black HCT MicroFoam Nitrile
Palm Coating

BENEFITS:

ANSI Abrasion Level 3,
"All in one" : Fit, Feel, Flexibility, Breathability, Durability
Excellent wet grip

CATEGORY:

Extraflex

APPLICATIONS:

General Assembly
Automotive Assembly
Handling Small Oily Parts
Maintenance
Warehousing



EN388



4121



Tested for harmful substances according to Oeko-Tex® Standard 100 SHCO 09266 TESTEX

SPECIFICATIONS

LINER MATERIALS	Gray Nylon Liner
COATING MATERIALS	Black HCT MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	XS -XXL

PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	120	120	120	120	120	120
CASE WEIGHT	11.01/lbs	11.89/lbs	12.56/lbs	15.42/lbs	16.52/lbs	17.62/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Light Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4121						
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:

