



T426LB
150 PSI Grey Food
S & D Hose **CORRUGATED**

3-A
 COMPLIANT MATERIAL

Applications:

Liquid, fatty, oily food and alcoholic beverage (max 75 proof) suction and discharge.

Hose may be sterilized with 5% soda solution.

★ **Not recommended for dry abrasive materials.**

Cover:

Grey NBR/PVC – abrasion, ozone and oil resistant.

Reinforcement:

High tensile textile cords with flexible steel helix wire.

Tube:

White NBR. Meets FDA and 3A (18-03) requirements.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T426 10 BAR (150 PSI) – GENERAL PURPOSE FOOD QUALITY – S & D (black letters)

Standard Length:

100 feet

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Vacuum HG (in.)	Min. Bending Radius (in. @ 68°F)	Weight (lbs./ft.)
T426LB300	3	76	3.62	92	150	30	6	1.84
T426LB400	4	102	4.65	118	150	30	8	2.69

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 36.

COUPLING SUGGESTIONS

Quick-Acting or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.